


S5000F

Changeover switch


base mounting 3P - 3P+N

Size 5

A 2000|2500|3150



	CODE-2000A	CODE-2500A	CODE-3150A
3P	S5F20003PP0	S5F25003PP0	S5F31503PP0
3P + N	S5F20003NP0	S5F25003NP0	S5F31503NP0



Technical information




tests:



According to IEC/EN 60947-3



			2000	2500	3150
Rated thermal current	I _{th} in ambient at 40° C 60% HR	A	2000	2500	3150
Rated insulation voltage	U _i	V	1000	1000	1000
Rated dielectric strength	50 Hz., 1 min.	V	10000	10000	10000
Rated impulse withstand voltage	U _{imp}	kV	8	8	8
AC Rated operational current ^{*(1)} (Rated operational frequency 50/60 Hz)	400V AC21A	A	2000	2500	3150
	400V AC22A	A	2000	2500	2500 ^{*(5)}
	500V AC21A	A	2000	2500	3150
	500V AC22A	A	2000 ^{*(5)}	2000 ^{*(5)}	2200 ^{*(5)}
	690V AC21A	A	2000	2500	2500
	690V AC22A	A	2000 ^{*(5)}	2000 ^{*(5)}	2000 ^{*(5)}
AC Rated operational power ^{*(2)}	800V AC20A	A	2000	2500	3150
	1000V AC20A	A	2000	2500	3150
	3x400V AC23A	kW	886,8	997,6	1108,5
	3x500V AC23A	kW	866	1108,5	1108,5
	3x690V AC23A	kW	956	956	956



Also available 4P changeover switches under request, consult reference

^{*(1)} Other voltages and / or utilization categories; please consult us
^{*(2)} Indicative values, value cos φ=0,8
^{*(3)} Without limiting protective device (short - circuit maintained 50 ms. - 200 ms.)
^{*(4)} Please consult us for more operations
^{*(5)} AC22B

Accessories



» Auxiliary contacts

1NA+1NC CODE DS-AU11
2NA+2NC CODE DS-AU12

I_e = 16 A (resistive loads)
4 A (inductive loads) at 250 Vac.




» Safety key lock device

Simple CODE D5LCB41
Double CODE D5LCF41

For external handle, lock the handle by means of a key in position "OFF" (under request, in "ON"), the key can only be removed with the handle locked

Panel drilling for handle and keylock device
Simple Double



Dimensions (mm)

Panel drilling for panel handle

