


THROUGH CONNECTORS

for Copper conductors




Conductor Size sqmm		Type	Dimensions mm		Quantity Box/Bag	Mechanical Tools	Hydraulic Tools
Low Stranded	Flexible		øi	L			
0,25÷1,5	0,25÷1,5	L03-M*	1,8	15	6.000/100	HN1	B15MD
1,5÷2,5	1,5÷2,5	L06-M*	2,4	15	4.000/100		
4÷6	4÷6	L1-M*	3,6	22	2.000/100	HN5	B15MD
10	10	L2-M	4,6	25	1.000/100		
16	16	L3-M	5,8	27	1.000/100	HN-A25	B15MD
25	25	L5-M	7,0	29	500/100		
35	25÷35	L7-M	8,9	33	400/100	TN70SE	B15MD
50	35÷50	L10-M	10,0	37	200/50		
70	50÷70	L14-M	11,3	39	200/50	TN120 SE*	B15MD
95	70÷95	L19-M	13,5	43	100/25		
120	95÷120	L24-M	15,2	47	100/25	TN120 SE*	B15MD
150	120÷150	L30-M	16,7	58	50/25		
185	150÷185	L37-M	19,2	64	50/25	TN120 SE*	B15MD
240	185÷240	L48-M	21,1	75	30/15		
300	240÷300	L60-M	23,7	90	20/10	TN120 SE*	B15MD
400	300÷400	L80-M	27,0	94	15/5		
500	400÷500	L100-M	30,3	98	12/1	TN120 SE*	B15MD
630	500÷630	L120-M*	33,4	105	12/1		
800	600	L160-M*	38,0	112	9/1	TN120 SE*	B15MD
1000	800	L200-M*	44,0	120	6/1		

*See page 127


L-M range of connectors are designed for jointing low voltage conductors.

Made of electrolytic Copper tube having the same dimension as A-M series lugs: L-M connectors are annealed and electrolytically Tin plated. They feature an internal taper at both ends to ease the introduction of the conductor and a central stop to ensure correct positioning. Details of the appropriate crimping tools and dies are shown on pages 230 to 231.



PARALLEL CONNECTORS

for Copper conductors



Total Conductor Size sqmm		Type	Dimensions mm		Quantity Box/Bag	Mechanical Tools	Hydraulic Tools
Low Stranded	Flexible		øi	L			
0,25÷1,5	0,25÷1,5	L03-P	1,8	6,0	10.000/100	HN1	B15MD
1,5÷2,5	1,5÷2,5	L06-P	2,4	6,0	5.000/100		
4÷6	4÷6	L1-P	3,6	9,0	3.000/100	HN5	B15MD
10	10	L2-P	4,6	10,5	3.000/100		
16	16	L3-P	5,8	11,5	2.000/100	HN-A25	B15MD
25	25	L5-P	7,0	13,0	1.500/100		
35	25÷35	L7-P	8,9	14,0	500/100	TN70SE	B15MD
50	35÷50	L10-P	10,0	16,0	500/100		
70	50÷70	L14-P	11,3	18,0	500/100	TN120 SE*	B15MD
95	70÷95	L19-P	13,5	19,0	300/50		
120	95÷120	L24-P	15,2	22,0	200/50	TN120 SE*	B15MD
150	120÷150	L30-P	16,7	26,5	100/50		
185	150÷185	L37-P	19,2	26,5	100/50	TN120 SE*	B15MD
240	185÷240	L48-P	21,1	34,0	60/15		
300	240÷300	L60-P	23,7	43,0	50/25	TN120 SE*	B15MD

*See page 127

Made of electrolytic Copper tube, having the same dimensions as A-M series lugs, L-P connectors are annealed and electrolytically Tin plated. They feature an internal taper to ease the introduction of the conductor. Details of the appropriate crimping tools and dies are shown on pages 230 to 231.



*Not UL approved